



PRODUCT SPECIFICATION

SPECIFICATION

Product Name: MOLIGA Li-Ca GREASE

DEFINITION

Produced with lithium, calcium soap and high quality paraffinic basestocks.

Provides effective lubrication where operating temperature is not high.

Water-resistant.

Provides superior protection against wear, rust and corrosion and extends the life of the system.

TYPICAL PROPERTIES*

METHOD

NLGI No	-	1	2	3
Colour	-	Light Brown	Light Brown	Light Brown
Soap Type	-	Lithium Calcium	Lithium Calcium	Lithium Calcium
Penetration, Worked 25 °C	ASTM D217	310-340	265-295	220-250
Dropping Point °C	ASTM D2265	Min 140	Min 140	Min 140
Base Oil Type	-	Mineral	Mineral	Mineral
Base Oil Viscosity 40 °C, cst	ASTM D445	100	100	100
Operating Temperature °C, max	-	-20/+100	-20/+100	-20/+100

Document Code	Revision No/Date	Page No	Prepared	Checked	Approved
KG-ÜS-204	10/14.10.2025	1/1	FACTORY HSEQ & LAB. MANAGER	MANAGEMENT REPRESENTATIVE	FACTORY MANAGER

* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical data about the products and product packagings, please contact with M Oil.