



# PRODUCT SPECIFICATION

# SPECIFICATION

## Product Name: MOLIGA MOLY GREASE

### DEFINITION

Produced with lithium soap and high quality paraffinic basestocks.

Contains Molibdendisulfid (MoS<sub>2</sub>) and EP additives. Thus provides additional protection against heavy loads and shock, prevents the contact of the metal with the metal at the vibration time.

High heat and water resistant.

Used at rolling element bearings, cams, railways, flat roller bearings.

Provides superior protection against wear, rust and corrosion.

TYPICAL PROPERTIES*		METHOD		
NLGI No	-	1	2	3
Colour	-	Black	Black	Black
Soap Type	-	Lithium	Lithium	Lithium
Penetration, Worked 25 °C	ASTM D217	310-340	265-295	210-240
Dropping Point °C	ASTM D2265	Min 180	Min 180	Min 180
Base Oil Type	-	Mineral	Mineral	Mineral
Base Oil Viscosity 40 °C, cst	ASTM D445	150	150	150
Operating Temperature	-	- 20 / +120	- 20 / +120	- 20 / +120

Document Code	Revision No/Date	Page No	Prepared	Checked	Approved
KG-ÜS-207	10/14.10.2025	1/1	FACTORY HSEQ & LAB. MANAGER	MANAGEMENT REPRESENTATIVE	FACTORY MANAGER