



## PRODUCT SPECIFICATION

## SPECIFICATION

**Product Name: MOLIGA WHITE GREASE**

### DEFINITION

Produced with lithium soap and high quality paraffinic basestocks.

Easily pumped at low temperatures, water-resistant.

Protects metal surfaces with anti-oxidation, anti-rust and anti-corrosion properties.

Ease of use of various temperature ranges.

Extends the life of the system with superior lubricity properties.

### TYPICAL PROPERTIES\*

### METHOD

NLGI No	-	00	0	1	2	3
Colour	-	Light Brown	Light Brown	Light Brown	Light Brown	Light Brown
Soap Type	-	Lithium	Lithium	Lithium	Lithium	Lithium
Penetration, Worked 25 °C	ASTM D217	400-430	355-385	310-340	265-295	220-250
Dropping Point °C	ASTM D2265	Min 170	Min 170	Min 175	Min 185	Min 190
Base Oil Type	-	Mineral	Mineral	Mineral	Mineral	Mineral
Base Oil Viscosity 40 °C, cst	ASTM D445	110	110	110	110	110
Operating Temperature °C, max		-20/+120	-20/+120	-20/+120	-20/+120	-20/+120

Document Code	Revision No/Date	Page No	Prepared	Checked	Approved
KG-ÜS-200	11/14.10.2025	1/1	FACTORY HSEQ & LAB. MANAGER	MANAGEMENT REPRESENTATIVE	FACTORY MANAGER

\* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical data about the products and product packagings, please contact with M Oil.