	PRODUCT SPECIFICATION	**SPECIFICATION**

Product Name

EOLO SUPER 2T / EOLO SUPER 2T

PRIMARY TESTS	**METHOD**	**SPECIFICATION**		
		MİN	TYP	MAX
Appearence	Visual		Clear and Bright	
Colour	ASTM D1500 / TS 1713 ISO 2049	2.5	3	4.5
Density 15'C, g/ml	ASTM D4052 / TS EN ISO 12185	0.880	0.890	0.910
Viscosity 100 'C, mm²/s	ASTM D445 / TS EN ISO 3104	9	11	14
Viscosity 40 'C, mm²/s	ASTM D445 / TS EN ISO 3104	80	110	150
Viscosity Index	ASTM D2270 / TS ISO 2909	90		

SECONDARY TESTS	**METHOD**	**SPECIFICATION**
Flash Point, 'C (COC)	ASTM D92 / TS EN ISO 2592	230
Pour Point, 'C	ASTM D97 / TS EN ISO 3016	-6
Sulfated Ash %m/m	ASTM D874 / TS ISO 3987	0,18

PERFORMANCE LEVELS : JAS0 FC / ISO-L-EGC / TISI API: TC

* As the defined values are typical values, there can be some little changes according to the production. M Oil keeps all the rights to update and change the formulations of products without making any announcements. For the updated informations and technical datas about the products and product packagings, please contact with M Oil.