



PRODUCT SPECIFICATION

SPECIFICATION

Product Name: MOLIGA WHITE GREASE EP

DEFINITION

Produced with lithium soap and high quality paraffinic basestocks.

Added extreme pressure additives and a multi-purpose grease.

With the ability to prevent excessive high pressure heavy, resistant to impact and vibration loads.

Extends the life of the system with superior lubricity properties.

High heat-resistant.

Easy to be pumped.

| TYPICAL PROPERTIES* | | METHOD | | | | |
|-------------------------------|------------|-------------|-------------|-------------|-------------|-------------|
| NLGI No | - | 00 | 0 | 1 | 2 | 3 |
| Colour | - | Light Brown |
| Soap Type | - | Lithium | Lithium | Lithium | Lithium | Lithium |
| Penetration, Worked 25 °C | ASTM D217 | 400-430 | 355-385 | 310-340 | 265-295 | 220-250 |
| Dropping Point °C | ASTM D2265 | Min 170 | Min 170 | Min 175 | Min 185 | Min 190 |
| Base Oil Type | - | Mineral | Mineral | Mineral | Mineral | Mineral |
| Base Oil Viscosity 40 °C, cst | ASTM D445 | 150 | 150 | 150 | 150 | 150 |
| Operating Temperature°C, max | - | -20/+120 | -20/+120 | -20/+120 | -20/+120 | -20/+120 |

| Document Code | Revision No/Date | Page No | Prepared | Checked | Approved |
|---------------|------------------|---------|-----------------------------|---------------------------|-----------------|
| KG-ÜS-201 | 10/14.10.2025 | 1/1 | FACTORY HSEQ & LAB. MANAGER | MANAGEMENT REPRESENTATIVE | FACTORY MANAGER |